S-80

The new generation of non-nuclear attack submarines



. O

Main Characteristics

· Overall Length
· Draught 6.3 metres
· Hull Diameter 7.3 metres
· Submerged Displacement
· Endurance 50 days
· Crew 32 + 8 special forces
· Surface Speed > 10 knots
· Submerged Speed > 19 knots

MISSIONS

- · Anti-Surface Warfare (ASuW)
- · Anti-Submarine Warfare (ASW)
- · Special Operations Forces (SOF)
- · Selective Land Attack
- · Designed for Full Combat Group Integration in First Strike Action
- · Shallow Water Operations
- · Intelligence, Surveillance and Reconnaissance (ISR)
- · Sequential Mine-laying
- · Deterrence

Main Performances

- Long Range Conventional Submarine Enhanced with Anaerobic Propulsion
- · Extremely Low Acoustic Signature
- · Excellent Manoeuvrability at Low Speed
- · Negligible Restrictions on 'Manoeuvring Limitations Diagram'
- · Highly automated Systems
- · Cutting Edge and High Range AIP System
- · Design for Low Life Cycle Cost

VESSEL CONCEPT

- · Single Hull
- · External Shape Optimised for Extremely low Acoustical Signature
- · Modular Design
- · Reduced Crew: 32 Crew
- · Stealth

POWER PLANT

- · AIP System (Ethanol Reformer + PEM fuel cell)
- · 3 Diesel Generators
- · Synchronous Electric Motor
- · 2 Battery Compartments (2 x 180 elements each)





COMBAT SYSTEM

- · High Performance Passive Acoustic Detection
- · High Performance Optronic Capabilities
- 6 Positive Discharge Tubes and Weapons Handling Capability for Missiles, Torpedoes and Mines
- · Torpedo Countermeasures System
- · Electronic Warfare System
- · High Level of Integration for Operation and C4I Optimum Information Management
- · State of the art Technology Based on OSA and Extensive Usage of COTS Flements
- · External and Internal Integrated Communications System, with High Data Rate Satellite Communications capability



